

Trelleborg Style Fluoroseal 450

## 1 PRODUCT AND COMPANY IDENTIFICATION

**Product Identifier:** Trelleborg Style Fluoroseal 450  
**Common Name:** Fluoroelastomer sheet  
**SDS Number:** 0821  
**Revision Date:** 2/9/2018

## 2 HAZARDS IDENTIFICATION

### Classification of Substance

**GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):**  
 Health, Respiratory or skin sensitization, 1 Skin

### GHS Label Elements, Including Precautionary Statements

**GHS Signal Word:** **WARNING**

**GHS Hazard Pictograms:**



**GHS Hazard Statements:**

H317 - May cause an allergic skin reaction

**GHS Precautionary Statements:**

P264 - Wash \_ thoroughly after handling.

### Hazards not Otherwise Classified (HNOC) or not Covered by GHS

**Route of Entry:** This material may enter the body through inhalation of nuisance dust.  
**Target Organs:** Respiratory system  
**Inhalation:** Sore, raspy throat  
**Skin Contact:** Redness and possible rash; itching  
**Eye Contact:** Itching and redness  
**Ingestion:** N/A

## 3 COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Ingredients		
CAS#	%	Chemical Name
0		Compounded fluoroelastomer rubber

## 4

## FIRST AID MEASURES

<b>Inhalation:</b>	Remove person to fresh air. If condition persists, seek medical attention.
<b>Skin Contact:</b>	Rinse with copious quantities of cool water. If rash or itching persists, seek medical attention.
<b>Eye Contact:</b>	Rinse with water. Do not rub eyes. Seek medical attention.
<b>Ingestion:</b>	Not applicable.

## 5

## FIRE FIGHTING MEASURES

Flash Point (Method Used): >250 C by TOC      Flammable Limits

LEL: N/A      UEL: N/A

Extinguishing Media: Water, carbon dioxide, or dry chemical

Special Fire Fighting Procedures: Thermal decomposition of fiber coating may produce an irritating mixture of smoke and fumes.

Unusual Fire and Explosion Hazards: None

## 6

## ACCIDENTAL RELEASE MEASURES

Material is a solid in roll form. If accidentally released, rewind material back onto roll.

## 7

## HANDLING AND STORAGE

<b>Handling Precautions:</b>	Use adequate material handling equipment.
<b>Storage Requirements:</b>	Store in dry place. Use may be at temperature extremes based on product data, but storage should be at ambient temperature.

## 8

## EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>Engineering Controls:</b>	Local exhaust; dust collection
<b>Personal Protective Equipment:</b>	HMIS PP, B   Safety Glasses, Gloves Safety glasses; cotton gloves; long sleeve clothing

Wash thoroughly with soap and water after handling

## 9

## PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Black Rubber	<b>Odor:</b>	Typical Rubber Odor
<b>Physical State:</b>	Solid	<b>Solubility:</b>	Negligible
<b>Specific Gravity or Density:</b>	2.4	<b>Freezing or Melting Point:</b>	N/A
<b>Boiling Point:</b>	N/A	<b>Vapor Density:</b>	N/A
<b>Vapor Pressure:</b>	N/A		
<b>Potentia Hydrogenii:</b>	N/A		

## 10

## STABILITY AND REACTIVITY

<b>Chemical Stability:</b>	Material is stable.
<b>Conditions to Avoid Identification:</b>	None known.
<b>Materials to Avoid Identification:</b>	Strong oxidizing agents.
<b>Hazardous Decomposition:</b>	Carbon monoxide; carbon dioxide; hydrogen fluoride
<b>Hazardous Polymerization:</b>	Will Not Occur.

Direct contact with fiberglass materials or exposure to airborne fiberglass dust may irritate the skin, eyes, nose and throat. Fiberglass can cause itching due to mechanical irritation from the fibers. This is not an allergic reaction to the material. Breathing fibers may irritate the airways resulting in coughing and a scratchy throat. Some people are sensitive to the fibers, while others are not.

No known hazards except for airborne fibers caused by nuisance dust. 10 milligrams per cubic meter for fiber diameters less than 7 microns.

Incineration preferred in a federal, state, or local approved facility.

Not hazardous product according to these transport classifications.


COMPONENT / (CAS/PERC) / CODES

None known


**NFPA:** Health = 3, Fire = 0, Reactivity = 0, Specific Hazard = n/a

**HMIS III:** Health = 2, Fire = 0, Physical Hazard = 0

**HMIS PPE:** B - Safety Glasses, Gloves



HMIS	
HEALTH	2
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	B



**Disclaimer:**

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).